

卧式锚机 Horizontal Windlass

卧式锚机

Horizontal Windlass

系列 Series: **GB Series** 目录页码 Catalogue page: **20, 21**

型号 Models: HP12.5, HP14, HP16, HP17.5, HP19, HP20.5



产品特点 Features

- 双绞缆，单链轮，但是您也可以根据自己需要选择安装双链轮
- 电机可正反转
- 当合上离合器装置时，锚链轮和绞缆筒可以分开工作
- 安装简单，没有需要安装在甲板以下的部分
- 需要检修或者保养时，不需要把锚机从甲板上拆下，只需要把锚链轮和绞缆筒拆下来就可以了
- 全封闭蜗轮蜗杆式减速箱
- 卧式锚机外壳是船用铸铝一体成型，白色环氧树脂喷塑
- 配手动开关，脚踏开关，换向器，把手
- 可选配置：电制有220V/380V可以选择，电机也可以选择单速或者双速配置
- 可选配置：单链轮 + 单绞缆筒
- 可选配置：单链轮 + 双绞缆筒
- 可选配置：双链轮 + 单绞缆筒
- 可选配置：双链轮 + 双绞缆筒
- Twin capstan, single gypsy, but you also can choose twin gypsy
- Reversible motor
- Independent operation of capstans and gypsy by declutching the drive
- Simple deck mounted installation with no under deck parts
- Simplified maintenance with ability to strip the running gear (chain-wheel and drum) from the windlass without disturbing the windlass mounting
- Totally sealed gearbox with ground worm drive
- Horizontal windlass casing are cast marine grade aluminium alloy with white epoxy enamel finish
- Fit include hand-switch, control box and wrench
- Option: AC 380V or 220V motor drive, double speed motor also available
- Option: Single gypsy single capstan
- Option: Single gypsy twin capstan
- Option: Twin gypsy single capstan
- Option: Twin gypsy twin capstan

技术参数 Specifications

规格型号 Specification

型号 Model	HP12.5	HP14	HP16	HP17.5	HP19	HP20.5
电机 Motor	3 /2.2KW	3.5KW	4KW	4KW	5.5KW	7.5KW
电源供电 Power Supply	220V/380V	380V/3PH	380V/3PH	380V/3PH	380V/3PH	380V/3PH
工作负载(kg) working Load(kg)	664	833	1088	1301	1534	1786

型号 Model	HP12.5	HP14	HP16	HP17.5	HP19	HP20.5
最大拉力 Max. Pull	996	1250	1632	1952	2301	2680
速度 Line speed	10	10	10.6	10.2	10.2	10.4
工作电流 AMPS@Working load	19.1/4.9	6.2A	8.2A	8.2A	11A	14.6A
参考净重(kg) Net Weight (kg)	205	260	320	410	490	530
锚链尺寸(mm) Chain Size/Gypsy(mm)	Stud Link- 12.5mm	Stud Link- 14mm	Stud Link- 16mm	Stud Link- 17.5mm	Stud Link- 19mm	Stud Link- 20.5mm

尺寸图 Dimensions

型号 MODEL	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)	H(mm)
HP12.5	850	420	840	460	132	450
HP14	850	428	870	460	137	450
HP16	880	450	930	500	145	490
HP17.5	900	480	1010	550	160	580
HP19	990	510	1100	560	185	630
HP20.5	1050	510	1240	680	202	740