

立式锚机 Vertical Windlass

立式锚机

Vertical Windlass

系列 Series: YD411–YD1011 / YD...H 目录页码 Catalogue page: 3, 4

型号 Models: YD411, YD411H, YD511, YD511H, YD611, YD611H, YD711, YD711H, YD811, YD811H, YD1011, YD1011H



产品特点 Features

- 立式锚机配合锚绳可以适用于机动船和帆船，也可以当作绞车用在大的船舶上，也可以用来辅助搬运。
 - 不锈钢316材质，高质量镜面抛光。
 - 锚链轮可以使用锚绳和锚链，每种锚机都有两种规格可供选择。
 - 配手动开关，脚踏开关，换向器，以及配套操作把手
 - 可选配置：带绞缆筒和不带绞缆筒两种类型可供选择
 - 可选配置：根据安装甲板厚度不同配置不同长度的固定螺栓
 - 可选配置：多种其他配套配件供选择，包含船锚，锚支架，链卡，锚链和锚绳
 - 可选配置：也可以配置交流电机
- Vertical design suits powerboats or sailboats and can be utilized for anchor ropes, as docking capstans on larger craft, or auxiliary line hauling.
 - High-quality polished 316 stainless steel surface makes for a beautiful appearance
 - Simplified installation by modular design and precise alignment of gearbox to the top works utilizing marine-grade stainless steel.
 - Rope-chain gypsy
 - Fit include hand-switch, foot-switch, control box and wrench
 - Option: With capstan & without capstan
 - Option: Different-length bolts for any deck thickness
 - Option: Full range of accessories including anchors, bow rollers, chain stoppers, chain & rope
 - Option: AC electric motor available

技术参数 Specifications

规格型号 Specification

型号 Model	YD411/YD411H	YD511/YD511H	YD611/YD611H	YD711/YD711H	YD811/YD811H	YD1011/YD1011H
电机 Motor	400W	600W	800W	1200W	1600W	2000W
电源供电 Power Supply	12V/24V	12V/24V	12V/24V	12V/24V	12V/24V	12V/24V
工作负载 Working Load	125 Kg	180 Kg	250 Kg	400 Kg	510 Kg	660Kg
最大拉力 Max. Pull	420 Kg	560 Kg	700 Kg	1200 Kg	1600 Kg	1900Kg
速度 Line speed	30m/ min	25m/min	20m/min	20m/min	20m/min	20m/min

型号 Model	YD411/YD411H	YD511/YD511H	YD611/YD611H	YD711/YD711H	YD811/YD811H	YD1011/YD1011H
工作电流 AMPS @Working load	30A/20A	60A/40A	100A/50A	120A/75A	165A/90A	170A/95A
净重 Net Weight	12/12.6Kg	12.3/12.6Kg	19/21Kg	24/25.5Kg	29/31.5Kg	30.5/33Kg
锚绳尺寸 Rope Size	14/16mm	14/16mm	18mm	18/20mm	18/20/26mm	20/26/28mm
锚链尺寸 Chain Size/ Gypsy	DIN766-6mm/7mm	DIN766-6mm/7mm	DIN766-8mm	DIN766-8mm/10mm	DIN766-8/10/12mm	DIN766-10/12/13mm

尺寸图 Dimensions

型号 Model	Motor(W)	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)	F(mm)	H(mm)	W(mm)
YD411	400	85	—	22-41	—	140	265	122	180
YD411H	400	—	59	22-41	115	135	265	122	181
YD511	600	85	—	22-41	—	140	275	122	180
YD511H	600	—	59	22-41	115	135	275	122	181
YD611	800	110	—	38-54	—	145	320	155	220
YD611H	800	—	79	38-54	165	145	320	155	220
YD711	1200	110	—	38-54	—	172	350	170	265
YD711H	1200	—	79	38-54	165	172	350	170	265
YD811	1600	110		38-54	—	190	415	170	265
YD811H	1600	—	79	38-54	165	190	415	170	265
YD1011	2000	130	—	38-54	—	190	415	195	295
YD1011H	2000	—	110	38-54	235	190	415	195	295